

NK-1100

- Remote control of NVRs, network video transmitters, network video receivers and network cameras via network connection
- Control of NVRs by using a USB mouse via network connection
- Two-way audio communication
- Convenient firmware upgrades via either the USB port or ethernet
- Firmware duplication and auto-recovery functions to enhance system stability
- Management of multiple network keyboards via network connection
- Programmable by using the LCD screen



SPECIFICATIONS

COMMUNICATION	
Interface	RS485(Terminal block), Ethernet(RJ45)
Baud Rate	300 bps ~ 115,200bps
Supports Protocols	Over 70 sorts of PTZ protocol (IDIS, PANASONIC, PELCO, SAUMSUNG, etc.)
Supports Devices	IP Camera, NVR, IDIS Solution Suite
Display	LCD(2 Line)
USB	1 port
Audio in/out	1(3.5mm) / 1(3.5mm)
Component	Joystick + Main Control Board
S/W Upgrade	USB, Network
SETUP Program	IDIS Discovery
GENERAL	
Dimensions (W x H x D)	377mm x 95mm x 178mm (14.8" x 3.7" x 7.0")
Weight	1.1kg (2.43lb)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)
Power Input	DC 5V, 3A
Approvals	FCC, CE, KC